



Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Safety Data Sheet

1 Identification

Energy Technology Group™

· Product identifier

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Energy Technology Group LLC 1660 Kensington Avenue, Suite <u>6</u> Cheektowaga NY 14215 (716) 240-4989

- · email of person responsible: wrichards@energytechnologygroup.com
- · Emergency telephone number:

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

2 Hazard identification

· Classification of the substance or mixture

Flammable Liquids - Category 3 H226 Flammable liquid and vapour.

Acute Toxicity (Oral) - Category 4 H302 Harmful if swallowed.

Acute Toxicity (Inhalation) - Category 4 H332 Harmful if inhaled.

Skin Irritation - Category 2 H315 Causes skin irritation.

Eye Irritation - Category 2A H319 Causes serious eye irritation.
Germ Cell Mutagenicity - Category 1B H340 May cause genetic defects.

Carcinogenicity - Category 1B H350 May cause cancer.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







- · Signal word Danger
- $\cdot \ \mbox{Hazard-determining components of labeling:}$

2-ethylhexyl nitrate

Solvent naphtha (petroleum), light arom.

2-butoxyethanol

1,2,4-trimethylbenzene

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

(Contd. on page 2)

Issue date: 07/22/2022 Last Revision Date: 07/22/2022 v 1

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 1)

· Precautionary statements

Obtain special instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fume/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents in accordance with local regulations.

- · Additional information: Restricted to professional users.
- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 2 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 2

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Chemical components:	
27247-96-7 2-ethylhexyl nitrate	25-50%
111-76-2 2-butoxyethanol	10-25%
64742-95-6 Solvent naphtha (petroleum), lig	nt arom. 2.5-10%
64742-94-5 Solvent naphtha (petroleum), he	avy arom. 2.5-10%
95-63-6 1,2,4-trimethylbenzene	≤2.5%
1330-20-7 xylene	≤2.5%
108-67-8 mesitylene	≤2.5%
178535-25-6 Benzene, ethylenated, residues,	distn. lights ≤2.5%
91-20-3 naphthalene	≤2.5%
100-41-4 ethylbenzene	≤2.5%
102-25-0 1,3,5-triethylbenzene	≤2.5%

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 2)

98-82-8 cumene

0.2% w/w

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor: Treat Symptomatically
 - Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Disorientation

Nausea

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

See section 11.

· Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
 - Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture See section 10 for additional information.
- Advice for firefighters
 - · Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 3)

· Environmental precautions:

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

See section 10 for incompatible materials.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol (20.0%)

EL TWA: 20 ppm EV TWA: 20 ppm

Skin

1330-20-7 xylene (2.2%)

EL STEL: 150 ppm TWA: 100 ppm

(Contd. on page 5)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

	(Contd. of page 4)
EV	STEL: 650 mg/m³, 150 ppm
	TWA: 435 mg/m³, 100 ppm
91-	·20-3 naphthalene (0.6%)
EL	TWA: 10 ppm
	Skin; IARC 2B
EV	STEL: 78 mg/m³, 15 ppm
	TWA: 52 mg/m³, 10 ppm
100	0-41-4 ethylbenzene (0.3%)
EL	TWA: 20 ppm
	IARC 2B
EV	STEL: 540 mg/m³, 125 ppm
	TWA: 435 mg/m³, 100 ppm
98-	82-8 cumene (0.2%)
EL	STEL: 75 ppm
	TWA: 25 ppm
	IARC 2B
EV	TWA: 245 mg/m³, 50 ppm
	Skin
	· Additional information. The lists that were valid during the creation were used as basis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
 - · Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Chemical resistant protective gloves

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· Body protection: Protective work clothing

CA

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 5)

9 Physical and chemical proper	ties
· Information on basic physical and c	hemical properties
· General Information	monitoria proportioo
Appearance:	
· Form:	Liquid
· Color:	Amber colored
· Odor:	Petrol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	162 °C
· Flash point:	51 °C
· Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density:	Not determined.
· Relative density at 20 °C	0.8-0.9
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
· Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent separation test	
· VOC content:	31.85 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 6)

- · Chemical stability
 - Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, open flames, sparks.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· Acute toxicity:		
· LD/	LC50 values that	are relevant for classification:
ATE (Acu	te Toxicity Estim	ate)
Oral	LD50	1,103 mg/kg
Dermal	LD50	2,235 mg/kg
Inhalative	LC50/4 h (vapor)	>17.2 mg/L
27247-96-	7 2-ethylhexyl nit	trate
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h (vapor)	11 mg/L (ATE)
111-76-2	2-butoxyethanol	
Oral	LD50	1,200 mg/kg (ATE)
		1,414 mg/kg (gpg)
Dermal	LD50	2,000 mg/kg (gpg)
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h (vapor)	>10.2 mg/L (rat)
95-63-6 1,	2,4-trimethylben	zene
Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h (vapor)	18 mg/L (rat)
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	6,700 mg/L (rat)
178535-25	, ,	rlenated, residues, distn. lights
Oral	LD50	>2,000 mg/kg (rat)
91-20-3 na	aphthalene	
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 7) 100-41-4 ethylbenzene Oral LD50 3,500 mg/kg (rat) Dermal LD50 17,800 mg/kg (rabbit) Inhalative LC50/4 h (vapor) 17.8 mg/L (rat) 98-82-8 cumene Oral LD50 1,400 mg/kg (rat) Dermal LD50 12,300 mg/kg (rabbit) Inhalative LC50/4 h (vapor) 24.7 mg/L (mouse)

· Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· 1/	· IARC (International Agency for Research on Cancer)		
111-76-2	2-butoxyethanol	3	
1330-20-7	xylene	3	
91-20-3	naphthalene	2B	
100-41-4	ethylbenzene	2B	
98-82-8	cumene	2B	
· N	· NTP (National Toxicology Program)		
91-20-3 na	aphthalene	R	
98-82-8 cı	ımene	R	
· C	· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.			

12 Ecological information

- · Toxicity
 - · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 8)

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable. · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

(petroleum), lig 1,2,4-trimethyll · ADR UN1993 Flamr (petroleum), li benzene, Ethyl · IMDG, IATA FLAMMABLE	mable liquids, n.o.s. (Solvent naphtha ght arom., Xylenes, 1,2,4-trimethyl-
(petroleum), li benzene, Ethyl · IMDG, IATA FLAMMABLE	ght arom., Xylenes, 1,2,4-trimethyl-
IMDG, IATA FLAMMABLÉ	(benzene)
(petroleum), lig benzene, ETH	LIQUID, N.O.S. (Solvent naphthaght arom., XYLENES, 1,2,4-trimethyl-
Transport hazard class(es)	
· DOT/TDG (Transport dangerous goods):	

·Class · Label

3 Flammable liquids

· IMDG, IATA



· Class 3 Flammable liquids · Label 3

(Contd. on page 10)

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 9) · Packing group DOT/TDG, ADR, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT/TDG Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1993 FLAMMABLE LIQUIDS, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM., XYLENES, 1,2,4-TRIMETHYLBENZENE, ETHYLBENZENE), 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions Contains no REACH candidate substance

· Sara

. 8	· Section 355 (extremely hazardous substances):		
None of the	None of the ingredients is listed.		
. 8	· Section 313 (Specific toxic chemical listings):		
	2-butoxyethanol		
95-63-6	1,2,4-trimethylbenzene		
1330-20-7			
91-20-3	naphthalene		
100-41-4	ethylbenzene		
98-82-8	cumene		
	(Contd. on page 11)		

.,

Issue date: 07/22/2022 v 1 Last Revision Date: 07/22/2022

Trade name: Pinnacle FBC PREMIUM YEAR 'ROUND DIESEL FUEL TREATMENT

(Contd. of page 10)

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Canadian substance listings:
 - · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

95-63-6 1,2,4-trimethylbenzene

108-67-8 mesitylene

100-41-4 ethylbenzene

· Canadian Ingredient Disclosure list (limit 1%)

111-76-2 2-butoxyethanol

- · National regulations:
 - · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact: Engineering Department
 - Date of the latest revision of the safety data sheet 07/22/2022 / -
 - · Issue Date 07/22/2022
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

CA