

EcoFuel™

HIGH-TECH TREATMENT AND CONDITIONER FOR TODAY'S DIESEL AND OTHER HYDROCARBON FUELS



EcoFuel™ is the all-season treatment to improve fuel efficiency, increase power, lower emissions, reduce engine wear, stabilize fuel, and eliminate the harmful effects of water in the fuel. EcoFuel™ is an organic-based product that is a powerful fuel system cleaner. It dissolves the gum, varnish, and carbon deposits that distort fuel injector spray patterns and damage delicate injector and pump components. Cleaning these parts allows your engine to operate with all the power and efficiency that the manufacturer designed into it.

EcoFuel™ is an organic surfactant which reduces the surface tension of the fuel, causing it to be atomized into smaller/finer droplets by the fuel injectors for more efficient combustion and reduced emissions.

With today's high-tech, electronically controlled engines, the need for a high-quality fuel treatment that meets the engine manufacturers' requirements is more important than ever before.

EcoFuel™

- chemically removes (dispersed) the water found in all diesel fuel which:
 - prevents corrosion of metal parts
 - prevents formation of damaging sulfuric acid
 - protects filters and fuel lines from icing
 - prevents the thick, sticky slime that clogs fuel injectors and plugs fuel filters (water supports the growth of spores and bacteria)
 - removes and prevents reformation of gums and varnishes that can clog fuel injectors and plug fuel filters
- acts as an antioxidant, significantly slowing the oxidation of hydrocarbon fuels and "stabilizing" them
- is a highly concentrated formula that uses only 8 ounces to treat 250 gallons
- contains no harmful alcohols that can damage gaskets and seals
- helps keep older equipment running longer and newer equipment running better
- is formulated with HPB™ - a proprietary water dispersion and surface tension reduction technology

*The powerful,
all-season,
organic-based
surfactant
fuel system cleaner.*

Features

- ✓ **IMPROVES FUEL ATOMIZATION FOR MORE POWER, GREATER EFFICIENCY, AND REDUCED EMISSIONS**
- ✓ **CHEMICALLY ELIMINATES WATER**
- ✓ **ORGANIC-BASED SURFACTANT FORMULA**
- ✓ **REDUCES OXIDATION TO STABILIZE FUEL**
- ✓ **CLEANS FUEL INJECTORS AND PUMPS**
- ✓ **CONTAINS NO HARMFUL ALCOHOLS THAT CAN DAMAGE GASKETS AND SEALS**
- ✓ **CAN BE SAFELY AND EFFECTIVELY USED IN DIESEL, BIODIESEL, HEATING FUELS, IFO, MFO, GASOLINE, GASOHOL, LP, NG, LNG, CNG, AND OTHER HYDROCARBON FUELS**




EcoFuel™

HIGH-TECH TREATMENT AND CONDITIONER FOR TODAY'S DIESEL AND OTHER HYDROCARBON FUELS



DIRECTIONS

- For best results, use every time you fuel, adding contents to fuel tank(s) prior to fueling. This will aid the mixing of the additive with the fuel.
- Use one ounce for each 31.25 gallons of fuel (1:4,000 treatment ratio).
- First-time users can use one ounce for each 15.6 gallons of fuel to speed the cleaning process.
- When operating in extreme conditions (marine, high humidity), it is acceptable to use one ounce for each 15.6 gallons of fuel on a regular basis.
- EcoFuel™ will eliminate its own volume of water.



EcoFuel™ PACKAGING

PACKAGE SIZE	TREATS	QUANTITY/CASE	PART NO.
2 oz. Bottle	15-60 US Gallons	24 per case	00100-F002
8 oz. Bottle	250 US Gallons	24 per case	00100-F008
32 oz. Bottle	1,000 US Gallons	6 per case	00100-F032
1 US Gallon	4,000 US Gallons	4 per case	00100-G001
2.5 US Gallons	10,000 US Gallons	2 per case	00100-G2.5
55 US Gallons	220,000 US Gallons	1 drum	00100-G055
270 US Gallons	1,080,000 US Gallons	1 tote	00100-G270
320 US Gallons	1,280,000 US Gallons	1 tote	00100-G320

PRODUCT STABILITY, STORAGE & HANDLING

STABILITY - PROPERTIES

Appearance: Clear liquid, colorless to pale yellow
Density: 910 (+/-20) kg/m³ at 60°F/15.5°C
Stability: -10°F/-23°C up to 176°F/80°C
Flash Point: 155°F/68°C

STORAGE

- This product should be stored above -10°F/-23°C.
- Keep product container tightly closed.
- Product container should be stored in a well-ventilated location.
- Stability, when stored as described, is 36+ months in an unopened container.

HANDLING

This product should be handled in the same manner and with the same precautions as diesel fuel.

For more information, please consult the Safety Data Sheet (SDS) for this product.

All used and unused product and its containers should be disposed of in accordance with all local, state, and federal regulations.

KEEP THIS PRODUCT OUT OF REACH OF CHILDREN.

Notice to Purchaser:

Energy Technology Group, LLC. provides no warranty of any kind with respect to the product whether expressed or implied, including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.



FOR ORDERING OR MORE INFORMATION, CONTACT:

ENERGY TECHNOLOGY GROUP, LLC | Buffalo, NY | p (716) 240-4989 | f (716) 402-5650
sales@energytechnologygroup.com | www.energytechnologygroup.com